



"The ART of Noise Control"

For your local ArtUSA Representative

Call: 1-888-454-6973

Internet: www.artusaindustries.us

Ultra Sound Absorption Baffles & Wall Panels



FEATURES:

- ★ "Ultra" Acoustical Performance
- ★ "Ultra" Durability
- ★ "Ultra" Cleanability
- ★ "Ultra" Affordability
- ★ "Ultra" Easy to Install



"The ART of Noise Control"

For your local ArtUSA Representative

Call: 1-888-454-6973

Internet: www.artusaindustries.us

Ultra Sound Absorption Baffles & Wall Panels

Acoustical Data:

Sound Absorption Coefficients -- Sabins Per 2' x 4' Baffle

One-Third Octave Band Center Frequencies (HZ)

Ultra Baffle	125	250	500	1000	2000	4000	NRC
Type "A"	1.15	5.26	8.0	10.9	9.34	5.5	8.4
Type "B"	1.00	8.09	14.65	15.72	12.68	4.93	12.8

Test method: ASTM C423-90a and C423-81

Sound Absorption Coefficients -- Sabins Per Wall Panel

One-Third Octave Band Center Frequencies (HZ)

Ultra Wall Panel	125	250	500	1000	2000	4000	NRC
4' x 4'	2.3	13.4	22.6	26.6	22.0	10.5	21.2
4' x 8'	4.6	26.8	45.3	53.2	44.0	21.0	42.3

Test method: ASTM C423-90a and C423-81

Specifications:

Ultra Baffles & Wall Panels

Product	Type	Sizes	Thickness	Core (cu. den.)
Ultra Baffle	A	2' x 4'	1 1/2"	1.6 lb.
Ultra Baffle	B	2' x 4' 4' x 4'	2" 2"	3.0 lb. 3.0 lb.
Ultra Wall Panel	W-2	2' x 6' 2' x 8'	1 1/2"	3.0 lb.
Ultra Wall Panel	W-4	4' x 4' 4' x 6' 4' x 8'	1 1/2"	3.0 lb.