



"The ART of Noise Control"

For your local ArtUSA Representative

Call: 1-888-454-6973

Internet: www.artusaindustries.us

Acousti™ Wall Panels Installation Guide

ArtUSA Acousti Wall Panels have a lightweight foam core and are simple to install with a wide range of methods. The panels attach in seconds to existing, clean surfaces. Choose from the mounting options below.

Foam Adhesive installation:



Clean wall surface.

Apply 1/4" bead of adhesive around panel perimeter on the fiberglass edge.

Apply a 1/4" bead from corner to corner through the center to create an "X."

Press panel to surface for 5 seconds.


Pull the panel away for approximately 1 minute to allow adhesive to become tacky.

Firmly press panel back into position.

AcouSTIC™ adhesive (part number PA-02) is a non-toxic, water-based adhesive that cleans up with soap and water. Each 10.5 ounce tube installs approximately 32 square feet of product. Tubes fit standard caulking guns or can be used with ArtUSA's applicator gun.



Hook & Loop Fastener Installation:



Prior to shipping, the loop side of the fastener is attached to the panel. The hook side is connected to the loop and has a tape backing. To install, just remove the tape backing and position the panel against the wall.

Concealed Spline Installation:



Panels come with kerfs along the panel edges and are equipped with a concealed spline attachment. The spline is inserted into one of the panels and installed on the wall. Connecting panels are inserted into the other half of the spline.

Z Clip Installation:



Before shipment, special Z clips are mounted to the back of the panel. Corresponding wall clips or wall bars are installed on the wall at the appropriate location to allow attachment of the panel.