



- Bold, geometric pattern
- Seamless installation
- Excellent acoustic control
- Panel size of 24" x 24" by 2", 3" or 4" thickness

**Applications:**

- Displays, showrooms and museums
- Machine rooms or manufacturing areas
- Modern offices and building interiors
- Recreational facilities
- Recording studios and listening rooms
- Restaurants and cafeterias

ArtUSA  
1-888-454-6975

**Pyramid Panels Product Information**

Pyramid Panels offer outstanding acoustic control across all frequencies with Noise Reduction Coefficient (NRC) ranging from 0.75 to 1.05. The unique geometric design of these panels dramatically increases the panels' surface area, providing much more acoustic control than flat surfaces. Pyramid Panels are made from Melamine foam, which is Class 1 fire-rated according to ASTM E 84 for flame spread and smoke density and also meets the corner burn test UL 1715.

Pyramid Panels, available in either natural or painted, can be easily mounted to any wall or ceiling surface with adhesive. Once installed, the 24" x 24" panels align to make an attractive, seamless pattern.

**Physical Data— foam**

Material Open-cell melamine-based foam	
Density 0.5 to 0.7 lbs./cubic ft. (ASTM D3574-77)	
Long-Term Service Temperature 302° F	
Fire Resistance Class 1 per ASTM E 84 (all finishes) Meets UL 1715 (willtec natural)	
Flame Spread per ASTM E 84 Natural: 5	Painted: 10
Smoke Density per ASTM E 84 Natural: 50	Painted: 10
Microbial Growth Passes UL 181, section 11	
Fungus Resistance Rating 0 per ASTM G21	
Finishes Natural (white and light grey) or painted	

**Sound Absorption**

Finish Thickness Coefficients per ASTM C423-90a

	Mounting									
	1	2	5	10	20	40	80	N	C	Type
Natural 2"	0.07	0.25	0.60	0.94	0.97	1.08	0.70	B		
(white and grey) 3"	0.09	0.37	0.81	1.01	1.03	1.07	0.80	B		
4"	0.18	0.44	0.96	1.14	1.18	1.19	0.95	B		

